



STRIPPING DIMENSION

NOTES: UNLESS OTHERWISE SPECIFIED

1. BODIES: BRASS PER JIS-C3604
2. CENTER CONTACT: BRASS PER JIS-C3604
3. INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710
4. CRIMP FERRULE: BRASS PER JIS-C2700
5. PART TO BE CLEAN AND FREE OF BURRS

APPROVED by \_\_\_\_\_ DATE: \_\_\_\_\_

7	CRIMP FERRULE	BRASS	1	NICKEL 100 $\mu$ " MIN.
6	CENTER CONTACT	BRASS	1	NICKEL 100 $\mu$ " MIN.
5	SHELL	BRASS	1	NICKEL 100 $\mu$ " MIN.
4	WASHER	BRASS	1	NONE
3	INSULATION II	POM	1	NONE
2	INSULATION I	POM	1	NONE
1	BODY	BRASS	1	NICKEL 100 $\mu$ " MIN.
NO	DESCRIPTION	MATERIAL	Q'TY	FINISH

DESCRIPTION		UHF STRAIGHT PLUG CRIMP						
製圖	DRAWN	TOLERANCE	品名	17-03-8 D.N.N 58U (50U)	日期	DATE	版次	REV.
	Elvis		XX					
檢圖	CHECK	XXX	單位	DWG.NO.	17-0027	佳楠精密電子股份有限公司 CHIN NAN PRECISION ELECTRONICS CO.,LTD.		
	Pony		mm(in)					
認定	APPROVAL	ANGLE	比例					
	Pony	±5°	4:1					